



BH207

Video Distribution Amplifier 1 in 4 out

Overview

The BH207 is a single channel Video Distribution Amplifier that will split a video signal into four identical outputs with no loss of signal strength or signal quality.

Its installer-friendly design has tool-less adjustable gain and high frequency lift controls. This stand-alone unit is fully RoHS compliant and also comes complete with 230V plug-top 12V DC power supply (110V available on request).



Technical Information

INPUT SIGNAL	Nominal 1.0V Pk-Pk @ 75Ω composite video signal. Suitable for either colour or monochrome video
OUTPUT SIGNAL AT UNITY GAIN	Nominal 1.0V Pk-Pk @ 75Ω (unit set to Unity Gain)
GAIN CONTROL	Differential Phase <3°. Differential Gain <3%
HF LIFT CONTROL	Variable from -2.0dB to +6.0dB
INPUT CONNECTOR	Variable from 0dB to +6.0dB @ 4.4MHz
OUTPUT CONNECTORS	BNC type coax connector
SURGE PROTECTION	Four BNC type coax connectors
POWER	Transorbs fitted as standard
OPERATING TEMP	12V DC 200 mW power consumption connected via spring loaded screw less terminal block
DIMENSIONS	-30°C to +45°C
MOUNTING	132mm L x 45mm W x 23mm H (excluding BNC connectors)
	Via 2 x 3.5mm holes for convenient screw fixing

Ordering Information

For a quotation, further details or technical support and advice, contact us by phone, fax or email, quoting part number BH207. Contact details are below.

Products available for use with BH207:

Part Number	Description
BH184	Video Launch Amplifier for unbalanced video signal, coax in/out
BH187	Line Corrector for unbalanced video signal, coax in/out

About Addlestone Electronics

The team at Addlestone Electronics have been designing and manufacturing specialist products for the CCTV industry for over 40 years. Our tradition of high quality and innovation has earned us an enviable reputation in the industry. We continue to lead the way with excellence in our field, offering first class support for users, distributors and installers and testing 100% of all products before dispatch from the factory.